

# EXTREME® 300 SERIES DOOR

Models EPD 300 & EPI 300 (insulated)



- ▶ Springless design allows 300,000 cycles of maintenance-free performance
- ▶ Operates at opening speeds of up to 24 inches per second
- ▶ Features APEX SmartController, for plug and play wiring with an LCD screen that makes door commissioning and limit setting simple
- ▶ Also available with an insulated curtain
- ▶ Can be upgraded to offer 500,000 cycles with a 3 year warranty\*\*

# EXTREME® 300 SERIES GRILLE

Models EPG324 (straight) & EPG324B (brick)



- ▶ Operates 3 times faster than the standard coiling grille
- ▶ Opening at speeds of up to 24" per second and closing at 12" per second
- ▶ Features APEX SmartController®, for plug and play wiring with an LCD screen that makes door commissioning and limit setting simple
- ▶ Requires no maintenance, other than routine checks and no replacement parts\*\*
- ▶ 2-year operator warranty and a 2 year / 300,000 cycle component warranty\*\*

# EXTREME® 1024 HIGH PERFORMANCE DOOR

Models EPD1024 & EPI1024 (insulated)



- ▶ Springless design allows 1,000,000 cycles of maintenance free performance
- ▶ Operates at speeds of up to 24 inches per second
- ▶ Low lifetime cost and low cost-per-cycle versus other high-performance slatted products
- ▶ Accepts virtually all activation systems
- ▶ Also available with an insulated curtain

# EXTREME® MICROCOIL® GRILLE

Models EPG324C & EPG324CB



- ▶ Smaller coil with nesting links, allows this grille to require nearly 50% less headroom when compared to other high-cycle grilles on the market
- ▶ Quietly operates at speeds of up to 24 in/sec
- ▶ Springless design requires no maintenance other than routine checks\*\*
- ▶ No replacement parts for up to 500,000 cycles
- ▶ 2-year operator warranty and a 2-year / 500,000 cycle component warranty\*\*

# EXTREME™ SERIES SECTIONAL DOOR

EX904N, EX3200N, & EX3700N Series Models



- ▶ Average of 24 in/sec opening speed is 3 times faster\* than a traditional sectional door
- ▶ 2yr / 50,000 cycle warranty\*\*
- ▶ Heavy duty components improve door life and promote smooth and quiet operation
- ▶ Up to 36 psf\*\*\* windload
- ▶ Available as insulated model to control temperature transfer and reduce noise

\*when compared to a 10'x10' door with a Logic 5.0™ operator set to an average of 8" per second

\*\*See warranty document for more information

\*\*\*based on size configuration and exposure

EXTREME SERIES™

800.294.4358

cooksondoor.com

COOKSON  
Preferred door solutions™

CornellCookson, LLC. is an ISO 9001:2015 registered company

5.2022